



PROVA 5637 Clamp-on Ground Resistance Tester

Electrical Specifications: (23°C ±5°C)

Ground Resistance (Auto range):

Range	Resolution	Accuracy of Reading ¹
0.025 - 0.250 Ω	0.002 Ω	± 1.5% ± 0.05 Ω
0.250 - 1.000 Ω	0.02 Ω	± 1.5% ± 0.05 Ω
1.001 - 9.999 Ω	0.02 Ω	± 1.5% ± 0.1 Ω
10.00 - 50.00 Ω	0.04 Ω	±2.0% ± 0.3 Ω
50.01 - 99.99 Ω	0.04 Ω	±2.0% ± 0.5 Ω
100.0 - 200.0 Ω	0.4 Ω	± 3.0% ± 1.0 Ω
200.1 - 400.0 Ω	2 Ω	± 5.0% ± 5 Ω
400.1 - 600.0 Ω	5 Ω	± 10% ± 10 Ω
600.1 – 1500 Ω	20 Ω	± 20%

¹ Loop resistance noninductive, external field < 200 A/m, external electrical field < 1 V/m, conductor centered.

² Resistance Measurement Frequency: 3.333KHz

High and Low Alarm

	Range	Resolution
High Alarm	0 - 1510Ω	1Ω
Lo Alarm	0 - 1510Ω	1Ω

Ground/ Leakage Current (Auto range, 50/60 Hz, True RMS, Crest Factor < 3.5)

Range	Resolution	Accuracy of Reading
0.300 - 1.000 mA	0.001 mA	± 2.0% ± 0.05 mA
1.00 - 10.00 mA	0.01 mA	± 2.0% ± 0.03 mA
10.0 - 100.0 mA	0.1 mA	± 2.0% ± 0.3 mA
100 – 1000 mA	1 mA	± 2.0% ± 3 mA

Ground/ Leakage Current (50/60 Hz, True RMS, Crest Factor < 3.5)


Range	Resolution	Accuracy of Reading
0.200 – 4.000 A	0.001 A	± 2.0% ± 0.03 A
4.00 – 35.00 A	0.01 A	± 3.0% ± 0.03 A

Accuracy of Resistance Calibration Plate: $\pm 0.5\%$

Data Logging Capacity : 116 records

Data Logging Interval: 1 to 255 seconds

General Specifications:

Conductor Size:	35 mm (1.38") approx.
Jaw Opening:	38 mm (1.49") approx.
Dimension:	276mm (L) x 100mm(W) x 47mm(H) 10.8" (L) x 3.9"(W) x 1.9"(H)
Battery Type:	9V IEC 6 LR61 (Alkaline)
Display:	4 digits 9999 counts LCD
Range Selection:	Auto
Overload Indication:	OL
Power Consumption:	40mA
Low Battery Indication:	
Battery Life:	3000 measurements
Sampling Time:	0.5 seconds
Operating Temperature:	0°C to 50°C (14°F to 122 °F)
Operating Humidity:	less than 85% relative
Altitude:	up to 2000M
Storage Temperature:	-20°C to 60°C (-4°F to 122 °F)
Storage Humidity:	less than 75% relative
Weight:	750g / 1.65 lbs
Accessories:	Resistance Calibration Plate x 1 9V Battery (Installed) x 1 Users Manual x 1 Carrying Case x 1

PROVA[®]

PROVA INSTRUMENTS INC.

Add: 6F-2, #129, Lane 235, Pao-Chiao Road,
Shin-Tien, Taipei Hsien 231, Taiwan

Tel: 886-2-89191255

Fax: 886-2-89191489

E-mail: prova@ms3.hinet.net